Windows 8

Open Command Prompt by swiping in from the right edge of the screen, tapping Search (or if you're using a mouse, pointing to the upper-right corner of the screen, moving the mouse pointer down, and then clicking Search), entering Command Prompt in the search box, and then tapping or clicking Command Prompt. At the command prompt, type:

netsh wlan delete profile name=tsu_secure On the Desktop screen, right-click the Wireless Icon located on the lower right hand corner of the screen, and select Open Network and Sharing Center. Select "Set up a new connection or network" and then click on Next.

Select "Manually connect to a wireless network" and then click on Next.

AES



Manually connect to a wireless network Connect to a hidden network or create a new wireless profile.

Enter information

Network name:

tsu_secure

Security type:

WPA2-Enterprise

Encryption type:

Network name needs to read: tsu_secure Security type should be set to WPA2-Enterprise.

Security Key:

Start this connect

Cancel Next

Choose "Next"

Change connection settings Open the connection properties so that I can change the settings.		Choose "Change connection settings"
tsu_secure Wireless Network Properties	Choose "Security "	" tab
Choose a network authentication method: Microsoft: Protected EAP (PEAP) Remember my credentials for this connection each time I'm logged on	ings Choose "Se work authe	ttings" next to "Choose a net- ntication method".
When connecting: Ur Validate server certificate	ncheck "Validate serve ecting"	er certificate" under "When con-
Method: AP-MSCHAP v2) Configure	Click "Configure" ne	xt to "Select Authentication Method"
EAP MSCHARy2 Properties	Uncheck "Automati and click OK.	cally use my Windows logon name"
Advanced settings Click "Advanced	ed settings" still in the	e Security tab.
Advanced settings 802.1X settings 802.11 settings	Check	"specify authentication mode:"

Click OK.

Sign into tsu_secure in the normal way by choosing it in your list of detected wireless networks and sign in using your tnstate credentials..

Save credentials

Specify authentication mode:

User authentication

Ŧ

		Wi	ndow	s 7
ETGEAR47	.atl			ă i
SU-BUS4	201			
ther Network	liter			
Open Network and Sharir	ng Center	Go to Ne	etwork and	Sharing Center.
Manage wireless netwo Change adapter setting Change advanced shar settings	orks (gs ring	Click "Mana	ige wireles	s networks" on far left.
tsu_secure	S	ecurity: WPA2-En	Right c	lick tsu_secure and choose Remove
	Proper	ties	networ	ŕk.
Manually create This creates a new ne for the network on y security key (if applic	e a network pro etwork profile or lo our computer. You cable).)file cates an existing networ need to know the netw	rk and saves a profile rork name (SSID) and	Choose Manually create a network profile.
Enter information			Network	name needs to read: tsu_secure
Network name:	tsu seci	ure	Security t	ype should be set to WPA2-
Security type:	WPA2-E	nterprise	Enterprise	e
Encryption type:	AES			
Encryption type: Security Key:	AES			
Encryption type: Security Key: V Start this connect	AES			

Change connection settings Open the connection properties so that I can change the settings.		Choose "Change connection settings"
tsu_secure Wireless Network Properties	Choose "Security "	" tab
Choose a network authentication method: Microsoft: Protected EAP (PEAP) Remember my credentials for this connection each time I'm logged on	ings Choose "Se work authe	ttings" next to "Choose a net- ntication method".
When connecting: Ur Validate server certificate	ncheck "Validate serve ecting"	er certificate" under "When con-
Method: AP-MSCHAP v2) Configure	Click "Configure" ne	xt to "Select Authentication Method"
EAP MSCHARy2 Properties	Uncheck "Automati and click OK.	cally use my Windows logon name"
Advanced settings Click "Advanced	ed settings" still in the	e Security tab.
Advanced settings 802.1X settings 802.11 settings	Check	"specify authentication mode:"

Click OK.

Sign into tsu_secure in the normal way by choosing it in your list of detected wireless networks and sign in using your tnstate credentials..

Save credentials

Specify authentication mode:

User authentication

Ŧ